

?

????????????/????????????? ?1 (converter/MUX E1 OS2E1) OS-2E1 OptiCin



2xE1+1xSFP 155Mbps, -48VDC & 220VAC

??????? : ??? ????????

????:

???? ? ? ???????:

????: 29700,00 ???.

[?????? ?????? ?? ????? ??????](#)

?????????????: [OptiCin](#)

?????????

????????????????? ?????????????? ?? ?????????? ?????????? ?????????????? ??? ?????? ?1 ?? ?????????????? ?????? ? ?????????????????? SFP
????????? 155Mbps ??? 1.25Gbps. ?????????????????? ?????????????????? ?? ?????? ?? ?????????? ?????-????? ? ?????????? PDH ??????????
?????????. 19" ?????? ? ??????? ??????? -48? ? 220? ?????????? ??????? ?????????? ??????????????????. ?????????? ?????????? ??????????????????
????????????? ?????? ?????????????????? ???????

?????????????:

- 2 ?? 2Mb/s ?????????? ????????????

- ?? 2-? E1 ????????

- Hotline Phone ????????

- ?????????? ??????? ?????????? ?????????? 175V-250? ?????????????? ?????? ??? -48? ?????????????? ?????

- 1U/19" ?????????????????? ???????

- ?????????????????? ?????????? ???????

E1 ??????????:

- Line Rate: 2.048Mbps+-50ppm

- Line Code: HDB3

- Jitter tolerance: fine then G.742, G823

- Interface Standard: ITU-T G.703

- E1 Impedance: 120Ohm (balance)

-
- Connector Type: RJ-45
 - SFP ??????????:
 - 20 pin SFP slot
 - ?????????????? ? SFP ???????? 155Mbps - 2.6Gbps
 - ????????????? ? ?????????????? ??????????????:
 - Dimension: Height 44 mm / 1.7 in (1U), Width 485 mm /19
 - Mounting: Stand-alone,19" inch rack mount, wall mount also available
 - Power Source: 175 – 250 VAC (50H/60Hz) or –48 VDC (-36 to –72VDC)
 - Power consumption: < 5 W
 - Temperature Range: 0°C - 50°C (32° to 122°F)
 - Relative Humidity: 0% - 90%, non-condensing

??????

??? ??????? ?? ????.