

?

????????????/????????????? ?1 (converter/MUX E1 OS4E1) OS-4E1 OptiCin



4xE1+1xSFP 155Mbps, -48VDC & 220VAC

??????? : ??? ????????

????? :

???? ?? ??????? :

???? : 37980,00 ???.

[??????? ?????? ?? ????? ??????](#)

????????????? : [OptiCin](#)

?????????

????????????????? ?????????????? ??? ?????????? ?????????? ?????????????? ?????????? ?1 ?? ?????????????? ?????? ? ?????????????????? SFP
????????? 155Mbps ??? 1.25Gbps. ?????????????? ?????????????? ??? ?????? ?? ?????????? ?????-????? ? ?????????? PDH ??????????
?????????. 19" ?????? ? ?????? ?????? -48? ? 220? ?????????? ?????? ?????????? ??????????????. ?????????? ?????????? ??????????????
????????? ?????? ?????????????????? ???????

????????????? :

- 4 ?? 2Mb/s ??????? ??????????

- ?? 4-? E1 ???????

- Fast Ethernet

- Hotline Phone ???????

- ?????????? ?????? ?????????? ?????????? 175V-250? ?????????????? ???? ??? -48? ?????????????? ????

- 1U/19" ?????????????? ???????

- ?????????????? ?????????? ???????

E1 ?????????? :

- Line Rate: 2.048Mbps+-50ppm

- Line Code: HDB3

- Jitter tolerance: fine then G.742, G823

- Interface Standard: ITU-T G.703

- E1 Impedance: 120Ohm (balance)

- Connector Type: RJ-45
- SFP ??????????:
- 20 pin SFP slot
- ??????????????? ? SFP ????????? 155Mbps - 2.6Gbps
- ?????????????? ? ??????????????? ??????????????????:
- Dimension: Height 44 mm / 1.7 in (1U), Width 485 mm /19
- Mounting: Stand-alone,19" inch rack mount, wall mount also available
- Power Source: 175 – 250 VAC (50H/60Hz) or –48 VDC (-36 to –72VDC)
- Power consumption: < 5 W
- Temperature Range: 0°C - 50°C (32° to 122°F)
- Relative Humidity: 0% - 90%, non-condensing

??????

??? ??????? ?? ??? ?????.