

?

????????????/????????????? ?1 (converter/MUX E1 OS4E1) OS-4E1 OptiCin



4xE1+1xSFP 155Mbps, -48VDC & 220VAC

??????? : ??? ????????

????:

???? ?? ???????:

????: 37980,00 ???.

[??????? ?????? ?? ????? ??????](#)

?????????????: [OptiCin](#)

?????????

????????????????? ?????????????? ??? ?????????? ?????????? ?????????????? ?????????? ??????? ?1 ?? ?????????????? ??????? ? ?????????????????? SFP
????????? 155Mbps ??? 1.25Gbps. ?????????????? ?????????????? ??? ?????? ?? ?????????? ??????-????? ? ?????????? PDH ??????????
?????????. 19" ?????? ? ??????? ??????? -48? ? 220? ?????????? ??????? ?????????? ??????????????. ?????????? ?????????? ??????????????
?????????? ?????? ?????????????????? ???????

?????????????:

- 4 ?? 2Mb/s ??????? ??????????

- ?? 4-? E1 ???????

- Fast Ethernet

- Hotline Phone ???????

- ?????????? ??????? ?????????? ?????????? 175V-250? ?????????????? ????? ??? -48? ?????????????? ?????

- 1U/19" ?????????????? ???????

- ?????????????? ?????????? ???????

E1 ??????????:

- Line Rate: 2.048Mbps+-50ppm

- Line Code: HDB3

- Jitter tolerance: fine then G.742, G823

- Interface Standard: ITU-T G.703

- E1 Impedance: 120Ohm (balance)

- Connector Type: RJ-45

SFP ??????????:

- 20 pin SFP slot

- ??????????????? ? SFP ????????? 155Mbps - 2.6Gbps

?????????????? ? ??????????????? ??????????????????:

- Dimension: Height 44 mm / 1.7 in (1U), Width 485 mm /19

- Mounting: Stand-alone,19" inch rack mount, wall mount also available

- Power Source: 175 – 250 VAC (50H/60Hz) or –48 VDC (-36 to –72VDC)

- Power consumption: < 5 W

- Temperature Range: 0°C - 50°C (32° to 122°F)

- Relative Humidity: 0% - 90%, non-condensing

??????

??? ??????? ?? ??? ?????.