

?

APC Smart-UPS 1000VA LCD RM 2U 230V



1000 VA, 700Watts, 2URack,LCD,230V,USB,SmartSlot

??????? : ?? ???????
????:

[?????? ?????? ?? ????? ??????](#)

?????????????: [APC](#)

????????

APC Smart-UPS 1000VA LCD RM 2U 230V

APC Smart-UPS, 700 Watts / 1000 VA, Input 230V / Output 230V , Interface Port RJ-45 Serial, SmartSlot, USB , Rack Height 2 U

Includes: CD with software, Documentation CD, Installation guide, Rack Mounting support rails, Smart UPS signalling RS-232 cable, USB cable

Output

Output Power Capacity 700 Watts / 1000 VA

Max Configurable Power 700 Watts / 1000 VA

Nominal Output Voltage 230V

Output Voltage Note Configurable for 220 : 230 or 240 nominal output voltage

Output Voltage Distortion Less than 5% at full load

Output Frequency (sync to mains) 57 - 63 Hz for 60 Hz nominal

Topology Line Interactive

Waveform Type Sine wave

Output Connections

(4) IEC 320 C13

(2) IEC Jumpers

Input

Nominal Input Voltage 230V

Input Frequency 50/60 Hz +/- 3 Hz (auto sensing)

Input Connections

IEC-320 C14

Input voltage range for main operations 160 - 280V

Input voltage adjustable range for mains operation 151 - 302V

Communications & Management

Interface Port(s) RJ-45 Serial, SmartSlot, USB

Available SmartSlot™ Interface Quantity 1

Control panel Multi-function LCD status and control console

Audible Alarm Alarm when on battery : distinctive low battery alarm : configurable delays

Emergency Power Off (EPO) Optional

Surge Protection and Filtering

Surge energy rating 459 Joules

Filtering Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

Physical

Maximum Height 89.00 mm

Maximum Width 432.00 mm

Maximum Depth 457.00 mm

Rack Height 2U

Net Weight 28.18 KG

Shipping Weight 31.45 KG

Shipping Height 251.00 mm

Shipping Width 594.00 mm

Shipping Depth 603.00 mm

Color Black

Units per Pallet 16.00

Environmental

Operating Environment 0 - 40 °C

Operating Relative Humidity 0 - 95%

Operating Elevation 0-3000 meters

Storage Temperature -15 - 45 °C

Storage Relative Humidity 0 - 95%

Storage Elevation 0-15000 meters

Audible noise at 1 meter from surface of unit 45.00 dBA

Online Thermal Dissipation 56.00 BTU/hr

Conformance

Regulatory Approvals C-tick, EN 50091-1, EN 50091-2, GOST, VDE

Standard Warranty 3 years repair or replace (excluding battery) and 2 year for battery

Environmental Compliance RoHS 7b Exemption,REACH: Contains No SVHCs

??????

?? ??????? ?? ??? ??????.