



IEC-320 C14

Input voltage range for main operations 160 - 286V

Input voltage adjustable range for mains operation 151 - 302V

Communications & Management

Interface Port(s) DB-9 RS-232, SmartSlot, USB

Available SmartSlot™ Interface Quantity 1

Control panel LED status display with load and battery bar-graphs and On Line : On Battery : Replace Battery : and Overload Indicators

Audible Alarm Alarm when on battery : distinctive low battery alarm : configurable delays

Emergency Power Off (EPO) Optional

Surge Protection and Filtering

Surge energy rating 320 Joules

Filtering Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

Physical

Maximum Height 216.00 mm

Maximum Width 170.00 mm

Maximum Depth 439.00 mm

Net Weight 18.86 KG

Shipping Weight 20.91 KG

Shipping Height 381.00 mm

Shipping Width 330.00 mm

Shipping Depth 584.00 mm

Color Black

Units per Pallet 24.00

Environmental

Operating Environment 0 - 40 °C

Operating Relative Humidity 0 - 95%

Operating Elevation 0-3000 meters

Storage Temperature -15 - 45 °C

Storage Relative Humidity 0 - 95%

Storage Elevation 0-15000 meters

Audible noise at 1 meter from surface of unit 41.00 dBA

Online Thermal Dissipation 100.00 BTU/hr

Conformance

Regulatory Approvals C-tick, CE, EN 50091-1, EN 50091-2, GOST, VDE

Standard Warranty 2 years repair or replace

Environmental Compliance RoHS 7b Exemption,China RoHS,REACH: Contains No SVHCs

??????

?? ????????? ?? ??? ???????.