

?

???????????????????????????????????? (UPS, ???) SUA750I APC



750VA,Inp.230V,Out.230V,RS-232,USB,SmartSlot,(RBC48)

????????: ??? ??????????
?????:

[???????? ?????? ?? ????? ??????](#)

????????????????: [APC](#)

?????????

APC Smart-UPS 750VA LCD 230V

APC Smart-UPS, 500 Watts / 750 VA, Input 230V / Output 230V , Interface Port SmartSlot, USB

Includes: CD with software, Documentation CD, Smart UPS signalling RS-232 cable, USB cable

Output

Output Power Capacity 500 Watts / 750 VA

Max Configurable Power 500 Watts / 750 VA

Nominal Output Voltage 230V

Output Voltage Distortion Less than 5% at full load

Output Frequency (sync to mains) 47 - 53 Hz for 50 Hz nominal,57 - 63 Hz for 60 Hz nominal

Topology Line Interactive

Waveform Type Sine wave

Output Connections

(6) IEC 320 C13

(2) IEC Jumpers

Input

Nominal Input Voltage 230V

Input Frequency 50/60 Hz +/- 3 Hz (auto sensing)

Input Connections

IEC-320 C14

Cord Length 1.83 meters

Input voltage range for main operations 160 - 280V

Input voltage adjustable range for mains operation 151 - 302V

Communications & Management

Interface Port(s) SmartSlot,USB

Available SmartSlot™ Interface Quantity 1

Control panel Multi-function LCD status and control console

Audible Alarm Alarm when on battery : distinctive low battery alarm : configurable delays

Emergency Power Off (EPO) Optional

Surge Protection and Filtering

Surge energy rating 540 Joules

Filtering Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

Physical

Maximum Height 161.00 mm

Maximum Width 138.00 mm

Maximum Depth 363.00 mm

Net Weight 13.18 KG

Shipping Weight 14.23 KG

Shipping Height 301.00 mm

Shipping Width 278.00 mm

Shipping Depth 499.00 mm

Color Black

Units per Pallet 40.00

Environmental

Operating Environment 0 - 40 °C

Operating Relative Humidity 0 - 95%

Operating Elevation 0-3000 meters

Storage Temperature -15 - 45 °C

Storage Relative Humidity 0 - 95%

Storage Elevation 0-15000 meters

Audible noise at 1 meter from surface of unit 40.00 dBA

Online Thermal Dissipation 90.00 BTU/hr

Conformance

Regulatory Approvals C-tick,CE,EN 50091-1,EN 50091-2,VDE

Standard Warranty 3 years repair or replace (excluding battery) and 2 year for battery

Environmental Compliance RoHS 7b Exemption,China RoHS,REACH: Contains No SVHCs

??????

?? ??????? ?? ??? ???????.