

?

????????? ?????????????????? ???????? (UPS, ???) SMT2200RMI2U APC



2200 VA, 1980Watts,2URack,LCD,230V,USB,SmartSlot

?????????: ??? ??????????
?????:

[????????? ???????? ?? ?????? ???????](#)

?????????????????: [APC](#)

?????????

APC Smart-UPS 2200VA RM 2U LCD 230V

Output

Output Power Capacity 1980 Watts/ 2200 VA

Max Configurable Power 1980 Watts/ 2200 VA

Nominal Output Voltage 230V

Output Voltage Note Configurable for 220 : 230 or 240 nominal output voltage

Output Frequency (sync to mains) 47 - 53 Hz for 50 Hz nominal,57 - 63 Hz for 60 Hz nominal

Other Output Voltages 220,240

Topology Line Interactive

Waveform Type Sine wave

Output Connections

(8) IEC 320 C13

(1) IEC 320 C19

(3) IEC Jumpers

Input

Nominal Input Voltage 230V

Input Frequency 50/60 Hz +/- 3 Hz (auto sensing)

Input Connections

British BS1363A

IEC-320 C20

Schuko CEE 7/EU1-16P

Cord Length 2 meters

Input voltage range for main operations 160 - 286V

Input voltage adjustable range for mains operation 151 - 299V

Other Input Voltages 220,240

Communications & Management

Interface Port(s) USB

Available SmartSlot™ Interface Quantity 1

Control panel Multi-function LCD status and control console

Audible Alarm Alarm when on battery : distinctive low battery alarm : configurable delays

Surge Protection and Filtering

Surge energy rating 375 Joules

Physical

Maximum Height 86.00 mm

Maximum Width 480.00 mm

Maximum Depth 683.00 mm

Rack Height 2U

Net Weight 42.31 KG

Shipping Weight 49.73 KG

Shipping Height 254.00 mm

Shipping Width 600.00 mm

Shipping Depth 980.00 mm

Units per Pallet 8.00

Environmental

Operating Environment 0 - 40 °C

Operating Relative Humidity 0 - 95%

Operating Elevation 0-3000 meters

Storage Temperature -15 - 45 °C

Storage Relative Humidity 0 - 95%

Storage Elevation 0-15000 meters

Audible noise at 1 meter from surface of unit 55.00 dBA

Online Thermal Dissipation 215.00 BTU/hr

Conformance

Regulatory Approvals C-tick,CE,EN 60950,EN/IEC 62040-1-1,EN/IEC 62040-2,GOST,GS Mark,IRAM,VDE,WEEE

Standard Warranty 3 years repair or replace (excluding battery) and 2 year for battery

Environmental Compliance RoHS 7b Exemption,REACH: Contains No SVHCs

?????

?? ?????? ?? ??? ??????.