

?

????????? ?????????????????? ???????? (UPS, ???) SMT3000I APC



3000 VA, 2700 Watts, LCD, 230V, USB, SmartSlot

?????????: ??? ??????????
?????:

[????????? ???????? ?? ?????? ???????](#)

?????????????????: [APC](#)

??????????

APC Smart-UPS 3000VA LCD 230V

Output

Output Power Capacity 2700 Watts/ 3000 VA

Max Configurable Power 2700 Watts/ 3000 VA

Nominal Output Voltage 230V

Output Voltage Note Configurable for 220 : 230 or 240 nominal output voltage

Output Voltage Distortion Less than 5% at full load

Output Frequency (sync to mains) 47 - 53 Hz for 50 Hz nominal, 57 - 63 Hz for 60 Hz nominal

Topology Line Interactive

Waveform Type Sine wave

Output Connections

(8) IEC 320 C13

(1) IEC 320 C19

(2) IEC Jumpers

Input

Nominal Input Voltage 230V

Input Frequency 50/60 Hz +/- 3 Hz (auto sensing)

Input Connections

IEC-320 C20

Schuko CEE 7 / EU1-16P

British BS1363A

Input voltage range for main operations 160 - 285V

Input voltage adjustable range for mains operation 151 - 302V

Communications & Management

Interface Port(s) SmartSlot,USB

Available SmartSlot™ Interface Quantity 1

Control panel Multi-function LCD status and control console

Audible Alarm Alarm when on battery : distinctive low battery alarm : configurable delays

Emergency Power Off (EPO) Yes

Surge Protection and Filtering

Surge energy rating 365 Joules

Filtering Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

Physical

Maximum Height 435.00 mm

Maximum Width 197.00 mm

Maximum Depth 544.00 mm

Net Weight 52.50 KG

Shipping Weight 63.70 KG

Shipping Height 699.00 mm

Shipping Width 381.00 mm

Shipping Depth 762.00 mm

Color Black

Units per Pallet 3.00

Environmental

Operating Environment 0 - 40 °C

Operating Relative Humidity 0 - 95%

Operating Elevation 0-3000 meters

Storage Temperature -15 - 45 °C

Storage Relative Humidity 0 - 95%

Storage Elevation 0-15000 meters

Audible noise at 1 meter from surface of unit 53.00 dBA

Online Thermal Dissipation 375.00 BTU/hr

Conformance

Regulatory Approvals C-tick,CE,EN 50091-1,EN 50091-2,VDE

Standard Warranty 3 years repair or replace (excluding battery) and 2 year for battery, optional on-site warranties available, optional extended warranties available

Environmental Compliance RoHS 7b Exemption,China RoHS,REACH: Contains No SVHCs

?????

??? ?????? ?? ???? ??????