

?

????????? ?????????????????? ??????? (UPS, ???) SUA1500I APC



1500 VA, USB, SmartSlot, ???, ???, RBC7

????????: ??? ?????????
????:

[???????? ??????? ?? ????? ???????](#)

?????????????: [APC](#)

?????????

APC Smart-UPS 1500VA USB & Serial 230V

APC Smart-UPS, 980 Watts / 1500 VA, Input 230V / Output 230V , Interface Port DB-9 RS-232, SmartSlot, USB

Includes: CD with software, Smart UPS signalling RS-232 cable, USB cable, User Manual

Output

Output Power Capacity 980 Watts/ 1500 VA

Max Configurable Power 980 Watts/ 1500 VA

Nominal Output Voltage 230V

Output Voltage Note Configurable for 220 : 230 or 240 nominal output voltage

Output Voltage Distortion Less than 5% at full load

Output Frequency (sync to mains) 47 - 53 Hz for 50 Hz nominal, 57 - 63 Hz for 60 Hz nominal

Topology Line Interactive

Waveform Type Sine wave

Output Connections

(8) IEC 320 C13

(2) IEC Jumpers

Input

Nominal Input Voltage 230V

Input Frequency 50/60 Hz +/- 3 Hz (auto sensing)

Input Connections

IEC-320 C14

Input voltage range for main operations 160 - 286V

Input voltage adjustable range for mains operation 151 - 302V

Communications & Management

Interface Port(s) DB-9 RS-232,SmartSlot,USB

Available SmartSlot™ Interface Quantity 1

Control panel LED status display with load and battery bar-graphs and On Line : On Battery : Replace Battery : and Overload Indicators

Audible Alarm Alarm when on battery : distinctive low battery alarm : configurable delays

Emergency Power Off (EPO) Optional

Surge Protection and Filtering

Surge energy rating 480 Joules

Filtering Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

Physical

Maximum Height 216.00 mm

Maximum Width 170.00 mm

Maximum Depth 439.00 mm

Net Weight 24.09 KG

Shipping Weight 27.00 KG

Shipping Height 370.00 mm

Shipping Width 330.00 mm

Shipping Depth 590.00 mm

Color Black

Units per Pallet 24.00

Environmental

Operating Environment 0 - 40 °C

Operating Relative Humidity 0 - 95%

Operating Elevation 0-3000 meters

Storage Temperature -15 - 45 °C

Storage Relative Humidity 0 - 95%

Storage Elevation 0-15000 meters

Audible noise at 1 meter from surface of unit 45.00 dBA

Online Thermal Dissipation 135.00 BTU/hr

Conformance

Regulatory Approvals C-tick,CE,EN 50091-1,EN 50091-2,GOST,VDE

Standard Warranty 2 years repair or replace

Environmental Compliance RoHS 7b Exemption,China RoHS,REACH: Contains No SVHCs

??????

??? ???????? ?? ????