

?

????????? ?????????????????? ???????? (UPS, ???) SUA2200I APC



2200VA, 230V, serial, USB, ???, ???, RBC55

????????: ??? ?????????
?????:

[???????? ?????? ?? ????? ??????](#)

?????????????: [APC](#)

?????????

APC Smart-UPS 2200VA USB & Serial 230V

Output

Output Power Capacity 1980 Watts/ 2200 VA

Max Configurable Power 1980 Watts/ 2200 VA

Nominal Output Voltage 230V

Output Voltage Note Configurable for 220 : 230 or 240 nominal output voltage

Efficiency at Full Load 95.0%

Output Voltage Distortion Less than 5% at full load

Output Frequency (sync to mains) 47 - 53 Hz for 50 Hz nominal, 57 - 63 Hz for 60 Hz nominal

Topology Line Interactive

Waveform Type Sine wave

Output Connections

(8) IEC 320 C13

(1) IEC 320 C19

(2) IEC Jumpers

Input

Nominal Input Voltage 230V

Input Frequency 50/60 Hz +/- 3 Hz (auto sensing)

Input Connections

IEC-320 C20

Schuko CEE 7 / EU1-16P

British BS1363A

Input voltage range for main operations 160 - 285V

Input voltage adjustable range for mains operation 151 - 302V

Communications & Management

Interface Port(s) DB-9 RS-232, SmartSlot

Available SmartSlot™ Interface Quantity 1

Control panel LED status display with load and battery bar-graphs and On Line : On Battery : Replace Battery : and Overload Indicators

Audible Alarm Alarm when on battery : distinctive low battery alarm : configurable delays

Emergency Power Off (EPO) Optional

Surge Protection and Filtering

Surge energy rating 365 Joules

Filtering Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

Physical

Maximum Height 432.00 mm

Maximum Width 196.00 mm

Maximum Depth 544.00 mm

Net Weight 50.92 KG

Shipping Weight 65.00 KG

Shipping Height 700.00 mm

Shipping Width 380.00 mm

Shipping Depth 760.00 mm

Color Black

Units per Pallet 3.00

Environmental

Operating Environment 0 - 40 °C

Operating Relative Humidity 0 - 95%

Operating Elevation 0-3000 meters

Storage Temperature -15 - 45 °C

Storage Relative Humidity 0 - 95%

Storage Elevation 0-15000 meters

Audible noise at 1 meter from surface of unit 45.00 dBA

Online Thermal Dissipation 275.00 BTU/hr

Conformance

Regulatory Approvals C-tick,CE,EN 50091-1,EN 50091-2,GOST,VDE

Standard Warranty 2 years repair or replace,optional on-site warranties available,optional extended warranties available

Environmental Compliance RoHS 7b Exemption

?????

?? ??????? ?? ??? ??????.